



技术要求(technical requirement)

- | | |
|---|--|
| 1、额定电压 (Rated voltage): 220-240VAC | 11、绝缘介电性能 (Dielectric strength): 1800VAC/1S during is without arcing |
| 2、额定频率 (Rated frequency): 50/60Hz | 12、旋转方向 (Rotation direction): CW/CCW |
| 3、额定转速 (Rated speed): 5/6r/min | 13、低压启动 (Start up with low voltage): 在额定频率0.85倍额定电压下, 其牵入转矩不低于标准值的0.7倍
Its pull in torque isn't less than 0.7times of standard value when it is under rating
freuency and 0.85 times of rating voltage |
| 4、额定功率: (Rated power) $\leq 4W$ | 14、未注公差按GB1804-92m级执行 Acting upon level GB1804-92m if there is no tolerance |
| 5、转矩 (Torque): $\geq 3kgf \cdot cm$ | 15、所用材料符合ROHS环保要求 The material used is in accordancewith ROHS environmental
protection requirement |
| 6、输入电流 (Input current): $\leq 20mA$ | |
| 7、绝缘等级 (Insulation class): Class B | |
| 8、噪声 (Noise): $\leq 40dB (A)$ | |
| 9、温升 (Temperature rise): $\leq 65K$ | |
| 10、绝缘电阻 (Insulation resistance): $\geq 100M \Omega$ | |